

TOWMASTER®

AMERICA'S BEST TRAILER



Description:

The Towmaster® TC provides the perfect value combining the features you need with the quality a Towmaster built trailer offers. This model works well for skid-loaders, mini-excavators and other small equipment and makes a great economical investment. The TC drop-deck is built on a solid cold-formed one-piece I-beam frame with 3-inch I-beam crossmembers and treated pine wood deck. It includes Dexter® Torflex® rubber torsion axles for a smooth ride, bolt-on parking jack, and solid-bar ramp hold-ups. This quality trailer offers the right amount of features, and excellent durability at a great price.

Quick Specs:

- 2" nominal treated pine wood deck
- 22.5" deck height (empty)
- 82" between fenders
- 14', 16', 18', or 20' deck (model specific)
- Dexter® Torflex® axles
- Forward adjusting electric brakes
- One-piece formed fender and inner panel
- Solid bar ramp hold-ups
- Grommet mounted incandescent lights

Photos may show optional equipment.



Formed frame and tongue provide a strong and integral structure for the trailer.



Sealed battery break-away system charges while plugged into the tow vehicle and can be checked at the press of a button.



Heavy-duty one-piece formed fender with backing plate keeps tire debris off equipment.

towmaster.com

800-462-4517

U.S.A. BUILT EMPLOYEE OWNED




GAUVANIZING AVAILABLE



Drop-Deck
TC-9D / TC-10D / TC-12D / TC-14D

TC-9D / TC-10D / TC-12D / TC-14D

AMERICA'S BEST TRAILER



SPECIFICATIONS

S=Standard O=Optional

CAPACITY / DIMENSIONS	TC-9D	TC-10D	TC-12D	TC-14D
Approx. Payload (lbs/kg)	7,500 / 3402	10,000 / 4536	12,000 / 5443	14,000 / 6350
GVWR (lbs/kg)	9,990 / 4531	12,600 / 5715	14,600 / 6622	16,600 / 7530
GAWR (lbs/kg)	12,000 / 5443	12,000 / 5443	12,000 / 5443	14,000 / 6350
Approx. Avg. Weight (lbs/kg)	2,600 / 1179	2,600 / 1179	2,600 / 1179	2,700 / 1225
Overall Length – 14' (ft-in/mm)	20-4 / 6198	20-4 / 6198	20-4 / 6198	N/A
Overall Length – 16' (ft-in/mm)	22-4 / 6807	22-4 / 6807	22-4 / 6807	22-4 / 6807
Overall Length – 18' (ft-in/mm)	24-4 / 7417	24-4 / 7417	24-4 / 7417	24-4 / 7417
Overall Length – 20' (ft-in/mm)	26-4 / 8027	26-4 / 8027	26-4 / 8027	26-4 / 8027
Deck Height (empty)(in/mm)	21.5 / 546	21.5 / 546	22.5 / 572	22.5 / 572
Overall Width (ft-in/mm)	8-6 / 2591	8-6 / 2591	8-6 / 2591	8-6 / 2591
Load Width (in/mm)	82 / 2083	82 / 2083	82 / 2083	82 / 2083
TONGUE				
Tongue Length 5'-0" (1524mm)	S	S	S	S
One-Piece Cold-Formed Tongue / Frame	S	S	S	S
Pintle Ring (in)	2.5	2.5	2.5	3
High-Tensile Safety Chain	3/8" Grade 43	3/8" Grade 43	3/8" Grade 43	3/8" Grade 70
Bolt-on Drop-Leg Parking Jack	7K	7K	7K	12K
FRAME / RAMPS				
Main Beam	6" I-Beam	6" I-Beam	High-Tensile W6 x 12	High Tensile W8 x 10
Crossmembers	3" Jr I-beam	3" Jr I-beam	3" Jr I-beam	3" Jr I-beam
Headboard Height (in / mm)	3 / 76	3 / 76	3 / 76	3 / 76
Deck Lip	N/A	N/A	N/A	N/A
Deck Material	2" nom. Treated Pine	2" nom. Treated Pine	2" nom. Treated Pine	2" nom. Treated Pine
Ramps (Ladder Style) Length x Width (ft-in x in/mm)	5-0x18 / 1524x470	5-0x18 / 1524x470	5-0x18 / 1524x470	5-0x18 / 1524x470
Load Angle (degrees)	17	17	17	19
Ramp Spring-Assist	O	O	O	O
Ramp Hold-ups	Solid Bar	Solid Bar	Solid Bar	Solid Bar
Tie Downs	Integrated Formed	Integrated Formed	Integrated Formed	Integrated Formed
Number of Tie-Downs (Total / Side)	8 / 4	8 / 4	8 / 4	8 / 4
SUSPENSION / TIRES				
Rubber-Ride Axles w/Warranty	S	S	S	S
Axle Capacity (each) (lbs/kg)	6,000 / 2721	6,000 / 2721	6,000 / 2721	7,000 / 3175
Axle Spread (in/mm)	34 / 864	34 / 864	34 / 864	34 / 864
Hubs	Standard Lube	Standard Lube	Standard Lube	Standard Lube
Electric Brakes w/Forward Adjust	S	S	S	S
Brake Size (in/mm)	12x2 / 305x51	12x2 / 305x51	12x2 / 305x51	12x2 / 305x51
Battery Break-Away Kit with Tow Charger	S	S	S	S
Wheels (in/mm)	16x6 / 406x152	16x6 / 406x152	16x6 / 406x152	16x6 / 406x152
Wheel Bolt Pattern	8-bolt	8-bolt	8-bolt	8-bolt
Tires / Load Range Rating	235/85R x 16 / E	235/85R x 16 / E	235/85R x 16 / E	235/85R x 16 / E

STANDARD EQUIPMENT

- Adjustable hitch height
- Weather resistant sealed modular wiring
- Grommet mounted incandescent lights
- Registration holder
- Rust inhibiting primer
- Durable, rust inhibiting top coat
- Die-cut UV resistant vinyl decals
- DOT conspicuity tape
- Mud flaps
- Adjustable ramp width spacing
- RV electrical plug
- Trailer color: Equipment black
- Ramp color: Equipment red

OPTIONAL EQUIPMENT

Other options may be available
See your dealer or visit our web site for details

- Hydraulic surge brakes
- 3" pintle ring or 2-5/16" ball coupler
- Gooseneck hitch
- 6-pole round electrical plug
- 12K parking jack
- Storage tray lid
- Pallet fork holders
- 8K electric winch
- Additional tie-downs
- D-ring tie-downs
- 3 ft. beavertail (comes with 4 ft. ramps)
- E-Z Lube hubs
- Spare tire and wheel mount
- Spare tire and wheel
- Tire upgrades available on select models
- Ramp lift springs
- Auto-Latch ramp hold-ups
- Several ramp options available
- LED lights
- Color options: Construction Yellow, Equipment Red, Equipment Blue, Equipment Charcoal
- Galvanizing

U.S.A. DESIGNED AND BUILT IN LITCHFIELD, MN

*Listed GVWR and weights are for reference only. Weights can vary due to options installed.

All dimensions are approximate. Check our website or see your authorized dealer for more information.

Manufacturer reserves the right to modify, change or discontinue models or options as seen fit without obligation to previously sold units. Written warranty covers each trailer. Photos may not show most recent changes to models.