



Deck-Over TC-18-3



Single-wheel tri-axle. 6K axles with spring-ride suspension.



Angle-iron beavertail and ramps provide excellent traction for loading and unloading.



One-way spring-assist ramps and grommet mounted LED lights.

Description:

The economical TC-18-3 is a great tri-axle trailer for mid-sized equipment. It's built on the Towmaster I-beam frame and features 3-inch I-beam crossmembers, 8'-6" wide oak wood deck, 5-foot angle-iron beavertail and 5-foot one-way spring assist ramps. Sealed wiring and grommet mounted LED lights are standard.

Quick Specs:

- 36" deck height (empty)
- 8'-6" wide white oak deck
- 20' deck
- 5' angle-iron beavertail
- D-ring tie-downs
- Electric brakes
- Slipper spring suspension
- One-way spring-assist ramps

towmaster.com

Photos may show optional equipment.


800-462-4517

**U.S.A. BUILT
EMPLOYEE OWNED**



**GALVANIZING
AVAILABLE**





SPECIFICATIONS

S=Standard O=Optional

TC-18-3

CAPACITY / DIMENSIONS

Capacity Rating (lbs/kg)	18,000 / 8165		
GVWR (lbs/kg)	24,200 / 10,977		
GAWR (lbs/kg)	18,000 / 8165		
Approx. Weight (lbs/kg)	6,200 / 2812		
Deck Length (ft-in/mm)	20-0 / 6096		
Overall Length (ft-in/mm)	31-2 / 9500		
Deck Height (empty)(in/mm)	36 / 914		
Overall Width (ft-in/mm)	8-6 / 2591		

TONGUE

Tongue Length (ft-in/mm)	5-0 / 1524		
Storage Tray	S		
Storage Tray Lid	O		
Pintle Ring (in)	3"		
High-Tensile Safety Chain (size - in)	3/8 Grade 70		
Bolt-on Drop-Leg Parking Jack	12K		

FRAME / RAMPS

Main Beam	W10 x 17, Gr. 50		
One-Piece Cold-Formed Frame Rails	S		
Crossmembers	3" Jr I-beam		
Headboard (in/mm)	5.5 / 140		
Channel Side Rails (in/mm)	6 / 152		
Deck Material	2" nom. White Oak		
Tie Downs	D-rings		
Tie Downs (Total/Side)	8 / 4		
Beavertail (ft-in / mm) (angle-degrees)	5-0 / 1524 (14)		
Beavertail Type	Angle-Iron		
Ladder Style Ramps (ft-in x in/mm)	5-0 x 21 / 1524 x 533		
Off-the-Ground Spring Assist	S		

SUSPENSION / TIRES

Slipper Spring Suspension	S		
No. of Axles	3		
Axle Capacity (each) (lbs/kg)	6,000 / 2722		
Axle Spread (in/mm)	36 / 914		
Hubs	Standard Lube		
Electric Brakes w/Forward Adjust	S		
Battery Break-Away Kit w/Tow Charger	S		
Brake Size (in/mm)	12x2 / 305x51		
Wheels (in/mm)	16x6 / 406x152		
Wheel Bolt Pattern	6-bolt		
Tires / Load Range Rating	235/85R16 / E		

STANDARD EQUIPMENT

- Adjustable hitch height
- Weather resistant sealed modular wiring
- Grommet mounted LED lights
- Registration holder
- Rust inhibiting primer
- Durable, rust inhibiting top coat
- Die-cut UV resistant vinyl decals
- DOT conspicuity tape
- Mud flaps
- Adjustable ramp width spacing
- RV electrical plug
- Trailer color: Equipment black
- Ramp color: Equipment red

OPTIONAL EQUIPMENT

Other options may be available. Ask your dealer or visit our web site.

- 2-5/16" ball coupler
- Gooseneck hitch
- 6-pole round electrical plug
- Storage tray lid
- 8K electric winch
- Additional tie-downs
- E-Z Lube hubs
- Spare tire and wheel mount
- Spare tire and wheel
- Ramp lift springs
- Several ramp options available
- Color options: Construction Yellow, Equipment Red, Blue, Charcoal
- Galvanizing

U.S.A. DESIGNED AND BUILT IN LITCHFIELD, MN

*Payload capacity is calculated by taking the GVWR and subtracting the trailer weight.

Listed GVWR, weights, and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.