



All dimensions are nominal. Illustration may be shown with optional equipment.

**Standard Features**

**Hitch/Tongue**

- Adjustable height, bolt-on coupler
- 3" pintle
- 7-Pole RV Plug
- One-piece cold-formed I-Beam frame rails
- Integrated storage tray (lid optional)
- 12K bolt-on, side-wind, parking jack
- Battery break-away kit with tow charger & test light
- Safety chains with hooks

**Frame/Deck**

- 82" load width, 19" deck height (fully loaded)
- Deck cushion cylinder
- Dual-point, single lever deck lock
- 6" I-beam main frame
- 3" channel crossmembers
- 2" nominal white oak deck
- D-ring tie-downs (4 per side)
- 12 gauge one-piece formed fender/panel

**Ramps/Tail**

- 24" knife edge approach plate (24" length is in addition to 16' or 18' deck length)
- 13°/12° load angle

**Axles/Suspension**

- Rubber-ride Torsion suspension axles
- (2) 8,000 lb. axles (4 wheels)
- Tires - 215/75R17.5 load range H, 16-ply
- 17.5" wheels, 8-bolt
- Electric brakes
- EZ Lube hubs

**Lights/Wiring**

- Rubber grommet mounted LED lights
- Sealed modular wiring harness

**Standard Features**

- Limited Lifetime Frame Warranty-10 years
- One-Year full Warranty
- 11 Year Suspension Warranty
- Weatherproof registration holder
- Two-component polyurethane primer and paint
- Trailer color: Equipment Black

Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Deck Width (in)	Deck Length (ft)
16,000	19,920	3,920	16,000	82"	16'
16,000	20,220	4,220	16,000	82"	18'

Other options may be available. Ask your dealer or visit our website.

Listed GVWR, weights and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.