



All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Hitch/Tongue

- Adjustable height, bolt-on coupler
- 3" pintle
- One-piece cold-formed I-Beam frame rails
- Integrated storage tray (lid optional)
- 12K bolt-on side-wind drop-leg parking jack
- Battery break-away kit with tow charger & test light
- 7-Pole round electrical plug
- Safety chains with hooks

Frame/Deck

- 20' tilt-deck (a stationary deck is optional)
- 102" load width
- 32.5" deck height (fully loaded)
- 10" I-Beam main frame
- 3" Jr. I-Beam crossmembers,
- 2" nominal white oak deck
- D-ring tie-downs (4 per side)

Ramps/Tail

- 16" (20°) approach ramp doubles as under-ride protection
- Tilt Deck Load Angle: 14.5°

Axles/Suspension

- Rubber-ride Torsion suspension axles
- (2) 8,000 lb. axles
- Tires - 215/75R17.5, load range H, 16-ply
- 17.5" wheels, 8-bolt (4 wheels)
- Electric brakes
- Forward self-adjusting brakes
- E-Z Lube hubs

Lights/Wiring

- Rubber grommet mounted LED lights
- Sealed modular wiring harness

Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year full Warranty
- 11-year Suspension Warranty
- Weatherproof registration holder
- Two-component polyurethane primer and paint

Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Deck Width (in)	Deck Length (ft)
16,000	21,280	5,280	16,000	102"	20'

Other options may be available. Ask your dealer or visit our website.

Listed GVWR, weights and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.

towmaster.com
800-462-4517

©Monroe Towmaster, LLC - 11.15.23 v1