



All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Hitch/Tongue

- Adjustable height hitch
- 3" pintle ring
- 7-Pole round electrical plug
- One-piece cold-formed I-Beam frame rails
- Integrated storage tray with lockable lid
- 12K bolt-on side-wind drop-leg parking jack
- Battery break-away kit with tow charger (electric brakes)
- Safety chains with hooks

Frame/Deck

- 24' tilt-deck, 4' stationary deck
- 102" load width, 34" deck height (fully loaded)
- Deck cushion cylinder
- Dual-point, single lever deck lock
- 10" I-beam main frame
- 3" Jr. I-beam crossmembers
- 2" nominal white oak deck
- D-rings (5 per side)

Ramps/Tail

- 16" (20°) approach ramp doubles as under-ride protection
- Tilt Deck Load Angle: 12°

Axles/Suspension

- Slipper spring suspension
- (2) 10,000 lb. axles (8 wheels)
- Tires - 235/85R16, load range F, 12-ply
- 16" wheels, 8-bolt
- Electric or Air brakes (Air has sensors on 1 axle, 2S/1M)
- Full ABS on air brakes
- Oil bath hubs
- Hutchens 9700 suspension-Optional

Lights/Wiring

- Rubber grommet mounted LED lights
- Sealed modular wiring harness

Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year full Warranty
- 6-year Suspension Warranty
- Weatherproof registration holder
- Two-component polyurethane primer and paint

Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Deck Width (in)	Deck Length (ft)
20,000	25,990	8,460	17,530	102"	24' (elec)
20,000	25,990	8,460	17,530	102"	24' (air)

Other options may be available. Ask your dealer or visit our website.

Listed GVWR, weights and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.

towmaster.com
800-462-4517

©Monroe Towmaster, LLC - 11.15.23 v1