



All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Hitch/Tongue

- Adjustable height hitch
- 3" pintle ring
- One-piece cold-formed I-Beam frame rails
- Integrated storage tray with lockable lid
- 12K bolt-on side-wind drop-leg jack
- Battery break-away kit with tow charger & test light
- 7-Pole round electrical plug
- Safety chains with hooks

Frame/Deck

- 20 ft. deck length
- 102" load width
- 34" deck height (fully loaded)
- 10" I-beam main frame
- 3" Jr. I-beam crossmembers
- 2" nominal white oak wood deck
- D-ring tie-downs (4 per side)

Ramps/Tail

- 5 ft. steel angle-iron beavertail (14° load angle)
- Beavertail to deck transition wood protectors
- 5 ft. x 21" ladder style angle iron cleated ramps
- Two-way spring-assist ramps

Axles/Suspension

- Hutchens 9700 adjustable suspension
- (2) 12,000 lb. axles (8 wheels)
- Tires - 235/85R16, load range F, 12-ply
- 16" wheels, 8-bolt
- Electric or Air brakes (Air has sensors on 1 axle, 2S/1M)
- Full ABS on air brakes
- Oil bath hubs

Lights/Wiring

- Rubber grommet mounted LED lights
- Sealed modular wiring harness

Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year full Warranty
- 6-year Suspension Warranty
- Weatherproof registration holder
- Two-component polyurethane primer and paint
- Trailer color: Equipment Black
- Ramp color: Equipment Red

Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Deck Width (in)	Deck Length (ft)
24,000	30,900	6,900	24,000	102"	20' (elec)
24,000	30,900	6,900	24,000	102"	20' (air)

Other options may be available. Ask your dealer or visit our website.

Listed GVWR, weights and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.

towmaster.com
800-462-4517

©Monroe Towmaster, LLC - 11.15.23 v1