



All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Hitch/Tongue

- Adjustable height hitch
- 3" pintle ring
- 7-Pole round electrical plug
- One-piece cold-formed I-Beam frame rails
- Integrated storage tray with lockable lid
- 25K bolt-on two-speed parking jack
- Safety chains with hooks

Frame/Deck

- 24' main deck length, 7' beavertail
- 102" load width, 32' deck height (fully loaded)
- Dual air bags
- Dual-point, single lever deck lock
- 10" I-beam main frame
- 3" Jr. I-beam cross members
- 2" nominal white oak deck
- D-ring tie-downs (4 per side)

Ramps/Tail

- 12° Beavertail
- 6' x 36" wood-topped Air-Ramps (10° load angle)

Axles/Suspension

- Hutchens 9700 adjustable suspension
- (2) 25,000 lb. axles
- Tires - 235/75R17.5 load range H, 16-ply
- 17.5" hub piloted wheels, 8-bolt (8 wheels)
- Air brakes (sensor on 1 axle, 2S/1M) Full ABS
- Brake size (12.25x7.5)
- Auto slack adjusters
- Oil bath hubs

Lights/Wiring

- Rubber grommet mounted LED lights
- Sealed modular wiring harness

Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year full Warranty
- 6-year Suspension Warranty
- Weatherproof registration holder
- Two-component polyurethane primer and paint

Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Deck Width (in)	Deck Length (ft)
45,000	52,350	12,350	40,000	102"	24'

Other options may be available. Ask your dealer or visit our website.

Listed GVWR, weights and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.

towmaster.com
800-462-4517

©Monroe Towmaster, LLC - 11.15.23 v1