



All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Hitch/Tongue

- Adjustable height, bolt-on coupler
- 2.5" pintle
- 7-Pole RV Plug
- 7K bolt-on, top-wind parking jack
- Battery break-away kit with tow charger & test light
- Safety chains with hooks

Frame/Deck

- 77" load width, 14" deck height (fully loaded)
- Single-point deck lock
- 4" I-beam main frame
- 3" Jr. I-beam crossmembers, 80,000 psi
- 2" nominal white oak wood deck
- 7" tall sides
- D-rings (3 per side)
- 12 gauge one-piece formed fender/panel

Ramps/Tail

- 12°/10° load angle

Axles/Suspension

- Rubber-ride Torsion suspension axle
- (1) 7,000 lb. axle (2 wheels)
- Tires - 235/85R16 load range F (12-ply)
- 16" wheels, 8-bolt
- Electric brakes
- Forward self-adjusting brakes
- E-Z Lube hubs

Lights/Wiring

- Rubber grommet mounted LED lights
- Sealed modular wiring harness

Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year full Warranty
- 11 Year Suspension Warranty
- Weatherproof registration holder
- Two-component polyurethane primer and paint
- Trailer color: Equipment Black

Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Deck Width (in)	Deck Length (ft)
7,000	8,000	2,000	6,000	77"	12'
7,000	8,230	2,230	6,000	77"	14'

Other options may be available. Ask your dealer or visit our website.

Listed GVWR, weights and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.

towmaster.com
800-462-4517
©Monroe Towmaster, LLC - 11.15.23 v1