



All dimensions are nominal. Illustration may be shown with optional equipment.

## Standard Features

### Hitch/Tongue

- Adjustable Height, Bolt-on Coupler
- 2.5" Pintle Ring
- 7-Pole RV Plug
- One-piece Cold Formed I-Beam Frame Rails
- Integrated Storage Tray (Lockable Lid Optional)
- 7k Bolt-on, Top-wind Parking Jack
- Battery Break-Away Kit with Tow Charger and Test Light
- Safety Chains with Hooks

### Frame/Deck

- 82" Between Fenders
- 18.5" Deck Height (Fully Loaded)
- 6" I-Beam Main Frame
- 3" Jr. I-Beam Crossmembers, 80,000 PSI
- 2" Nominal Treated Pine Wood Deck
- Formed Flat Bar Tie Downs (4 Per Side)
- 12 Gauge One-Piece Formed Fender/Panel

### Ramps/Tail

- 18" x 5'-0" Formed Sides, Cleated Ladder Style
- Solid-Bar Pinned Ramp Hold-Ups
- Load Angle: 17°

### Axles/Suspension

- Rubber-Ride Torsion Suspension Axles
- (2) 6,000 lb. Axles (4 Wheels)
- Tires-235/85R16, Load Range F, 12-Ply
- 16" Wheels, 6 Bolt
- Electric Brakes
- Forward Self-Adjusting Brakes
- Standard (Non-EZ Lube) Hubs
- 34" Axle Spacing

### Lights/Wiring

- Rubber Grommet Mounted LED Lights
- Sealed Modular Wiring Harness

### Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year Full Warranty
- 10 Year Suspension Warranty
- Weatherproof Registration Holder
- Two-Component Polyurethane Primer and Paint
- Trailer Color: Equipment Black
- Ramp Color: Equipment Red

| GAWR (lbs.) | GVWR (lbs.) | Weight (lbs.) | Capacity (lbs.) | Deck Width (in.) | Deck Length (in.) |
|-------------|-------------|---------------|-----------------|------------------|-------------------|
| 12,000      | 14,790      | 2,790         | 12,000          | 82"              | 16'               |
| 12,000      | 14,990      | 2,990         | 12,000          | 82"              | 18'               |

Other Options May Be Available. Ask Your Dealer or Visit our Website.

Listed GVWR, weight and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our website or your local authorized dealer for more information.

| Options  | TC-12D | TC-14D |
|--|--------|--------|
| <b>TONGUE/HITCH</b>  |        |        |
| Hydraulic Surge Brakes with Free Backing (Check Local D.O.T Laws)  | •      | •      |
| 2-5/16" Ball Coupler   | •      | •      |
| 3" Pintle Ring   | •      |        |
| 4-Way Flat Electrical Plug   | •      |        |
| 6-Pole Round Electrical  | •      | •      |
| 7-Pole Round Electrical  | •      | •      |
| 12k Drop-Leg, Side-Wind Jack (In Lieu of 7K)   | •      |        |
| 12k Spring Foot Jack   | •      |        |
| 12k Spring Foot Jack   |        | •      |
| 25k Two-Speed Parking Jack   |        | •      |
| Lockable Storage Tray Lid (Storage Tray Standard)  | •      | •      |
| Mesh in A-Frame of Tongue  | •      | •      |
| A-Frame Gooseneck (2-5/16" coupler) 84" swing clearance, 39" hitch height/truck bed height (please call if your measurement is different). A toolbox, toolbox lid and dual 12k jacks are included. | •      | •      |
| Spare Tire Mount on A-Frame Gooseneck (Spare Tire Sold Separately)   | •      | •      |
| A-Frame Gooseneck Toolbox (lockable) Mounted Between the Gooseneck Uprights, Includes a Chain Bar  | •      | •      |
| <b>MAIN DECK/BEAVERTAIL</b>  |        |        |
| Pallet Fork Holders  | •      | •      |
| Additional Flat Bar Tie-Downs  | •      | •      |
| D-Ring Tie-Downs   | •      | •      |
| White Oak Decking in Lieu of Pressure Treated Pine Wood  | •      |        |
| Apitong Wood Decking Upgrade   | •      | •      |
| 7-Gauge Steel Deck in Lieu of Pressure Treated Pine Wood, with Non-Slip Grit   | •      | •      |
| 3/16" Diamond Plate Steel Decking. Crossmembers 12" On-Center  | •      | •      |
| Rub Rail and Stake Pockets in Lieu of Flat Bar Tie Downs   | •      | •      |
| 3-foot Wood-Topped Beavertail with 5' Angle-Iron Ramps (10 Degree Load Angle)  | •      | •      |
| 3-Foot Angle Iron Beavertail with 5' Angle-Iron Ramps (10 degree load angle)   | •      | •      |
| <b>SUSPENSION/TIRES AND WHEELS</b>   |        |        |
| EZ Lube Hubs   | •      | •      |
| Hubodometer-Mounts on Wheel to Measure Distance Traveled   | •      | •      |
| Spare Tire Mount Bracket, Mounted Curbside in Front of the Fender (Not to be used with Rub Rail)   | •      | •      |
| Spare Tire and Wheel 235/85R16 Load Range "F"  | •      | •      |
| Spare Tire and Wheel 235/85R16 Load Range "G"  | •      | •      |
| 235/85R16 Load Range "G" 14-Ply Upgrade (in lieu of "F") set of Four Tires   | •      | •      |

| Options   | TC-12D | TC-14D |
|---|--------|--------|
| <b>RAMPS</b>  |        |        |
| Spring Assist Ramp Kit  | •      | •      |
| Auto-Latch Ramp Hold-Up System  | •      | •      |
| Wood Filled 5-Foot Ramps (Pair)   | •      | •      |
| Full Width Mesh-Top Ramps. Two ramps 48" wide x 5'-0" Long Each. Solid-Bar Ramp Hold-Ups with Spring Assist Included. | •      | •      |
| 5'-0" Ramps with Star Traction and Solid Ramp Hold-Ups  | •      | •      |
| 6'-0" Ramps with Star Traction and Solid-Bar Ramp Hold-Ups (Improves Load Angle by 2 Degrees versus 5'-0" ramps)      | •      | •      |
| 6'-0" Ramps, Cleated Ladder Style with Solid-Bar Ramp Hold-Ups (Improves Load Angle by 2 Degrees versus 5'-0" ramps)  | •      | •      |
| <b>PAINT/ELECTRICAL/OTHER</b>   |        |        |
| 8K Electric Winch with 95 Feet of 5/16" Cable, Mounted on the Deck Side of Headboard, Includes a Battery and Charger  | •      | •      |
| Trailer Color Options: See Standard Color Chart   | •      | •      |
| Galvanizing-(Please Call for Current Cost)  | •      | •      |
| Custom Paint Color: Market Price (Please Call for Cost)   |        |        |
| Two Chock Blocks with Holders (Mounted on Front of Fenders)   | •      | •      |
| Change Ramp Color from Red to Yellow, or Blue or Charcoal (No Charge for Black)                                       | •      | •      |