



All dimensions are nominal. Illustration may be shown with optional equipment.

### Standard Features

#### Hitch/Tongue

- Adjustable height, bolt-on coupler
- 3" pintle
- 7-Pole RV Plug
- One-piece cold-formed I-Beam frame rails
- Integrated storage tray (lid optional)
- 12K bolt-on, side-wind, drop-leg parking jack
- Battery break-away kit with tow charger & test light
- Safety chains with hooks

#### Frame/Deck

- 82" between fenders
- 21.5" deck height (fully loaded)
- 8" I-beam main frame
- 3" Jr. I-beam crossmembers, 80,000 psi
- 2" nominal white oak wood deck
- Formed flat bar tie downs (4 per side)
- 12 gauge one-piece formed fender/panel

#### Ramps/Tail

- 18" x 5'-0" channel sides, cleated ladder style
- Load angle: 19°
- Solid-bar pinned ramp hold-ups

#### Axles/Suspension

- Rubber-ride Torsion suspension axles
- (2) 7,000 lb. axles (4 wheels)
- Tires - 235/85R16, load range F, 12-ply
- 16" wheels, 8-bolt
- Electric brakes
- Forward self-adjusting brakes
- Standard (non-EZ Lube) hubs

#### Lights/Wiring

- Rubber grommet mounted LED lights
- Sealed modular wiring harness

#### Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year full Warranty
- 11 Year Suspension Warranty
- Weatherproof registration holder
- Two-component polyurethane primer and paint
- Trailer color: Equipment Black
- Ramp color: Equipment Red

Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Deck Width (in)	Deck Length (ft)
14,000	17,180	3,180	14,000	82"	16'
14,000	17,380	3,380	14,000	82"	18'
14,000	17,500	3,500	14,000	82"	20'

Other options may be available. Ask your dealer or visit our website.

Listed GVWR, weights and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.