



All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Hitch/Tongue

- Adjustable height, bolt-on coupler
- 2-5/16" ball coupler
- 7-Pole RV Plug
- Steel toolbox with gas springs
- Power up/gravity down pump
- Corded remote for hydraulic pump 25ft
- 12K bolt-on side-wind spring return jack
- Battery break-away kit w/tow charger & test light
- On board 110-volt charger
- Safety chains w/hooks

Frame/Dump Body

- 82" dump body inside diameter width
- 7 gauge, one-piece steel floor
- 24" tall, 11 gauge steel sides
- 28.5" bed height (unloaded)
- 6" x 2" steel tube main frame (channel tongue)
- 16" Crossmember Spacing (Grade 50)
- Stake pockets (4 per side)
- D-Rings (5 mounted on dump floor)
- Steel tread plate fender
- Two-way double doors
- Spare tire mount
- Tarp kit
- 6' ramps with underbody storage

Axles/Suspension

- Slipper Spring suspension
- (2) 7,000 lb. axles (4 wheels)
- Tires - 235/80R16 load range E, 10-ply
- 16" wheels, 8-bolt
- Electric brakes
- Forward self-adjusting brakes
- EZ-Lube Hubs

Lights/Wiring

- LED lights
- 12-volt Deep Cycle Battery

Standard Features

- Limited Lifetime Frame Warranty
- One-Year full Warranty
- 6 Year Suspension Warranty
- Two-component polyurethane primer and paint
- Trailer color: Equipment Black
- Ramp color: Equipment Black

*Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Dump I.D. Width (in)	Dump Length (ft)
14,000	15,900	3,900	12,000	82"	14'
14,000	16,150	4,150	12,000	82"	16'

Other options may be available. Ask your dealer or visit our website.

Listed GVWR, weights and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.

towmaster.com
800-462-4517

©Monroe Towmaster, LLC - 11,15,23 v1