

# A-Frame Gooseneck

**Trailer Option** 



More Strength. More Stability. More Storage. Take on bigger jobs with our A-frame gooseneck, designed to shift more weight to your tow vehicle for greater hauling capacity and stability. It features an 84" swing clearance, a 39" truck clearance height, and comes standard with a 2-5/16" gooseneck coupler, with an optional fifth-wheel king-pin hitch for added versatility. Plus, the built-in tool tray keeps your gear secure and within reach because efficiency matters.

## **Highlights**

- **Increased weight distribution:** the A-frame design allows for better weight distribution to the tow vehicle.
- Improved maneuverability: the gooseneck hitch connection allows for a tighter turning radius and easier navigation compared to bumper pull trailers.
- Better weight transfer: with the hitch over the truck's rear axle, weight is better distributed to the towing vehicle, leading to improved stability and braking performance
- More cargo space and versatility: includes a standard integrated lockable toolbox on top of the gooseneck. For additional storage, an optional lockable chain box with a chain bar can be mounted between the gooseneck frame uprights. Also allows for an optional top deck to further expand capacity.
- Long lasting finish: our advanced polyurethane paint system, combined with a rust-inhibiting primer, provides superior durability and weather resistance. Comes with a 3-year paint warranty.

#### Your benefits

- Customization: select your hitch type and adjust the fifth-wheel height to match your tow vehicle's configuration, ensuring a precise and secure fit for your hauling needs.
- **Versatile compatibility:** available on multiple different trailer models, providing the flexibility to tackle a wide range of jobs with confidence and efficiency.
- **Industry leading warranty:** our frames are manufactured to last, so we offer an industry leading lifetime frame warranty.
- Quality and ROI: built for durability and performance, our trailers offer long-term value with minimal maintenance costs. Backed by an industry leading warranty, we provide a superior return on investment by keeping your equipment on the road longer, ensuring reliability for years to come.



# **Gallery**







## **Technical data**

	A-Frame Gooseneck
Hitch	
Coupler height	39"
Standard hitch	2-5/16" gooseneck coupler
Optional hitch	King-Pin gooseneck coupler
Measurements	'
Swing clearance	84"
Standard height	39"
Standard equipment	'
Parking jacks	Dual parking jacks
Wiring	Weather resistant sealed modular wiring
Paint	Rust inhibiting primer, durable top coat
Color	Match to trailer
Electric	RV Electrical plug
Storage	Tool tray with lid
Safety	
Chains	Safety chains with hooks
Visibility	DOT approved conspicuity tape
Convenience	Registration holder
Optional equipment	
Swing clearance	Custom per customer spec
Winch option	Gooseneck mounted winch
Upgraded coupler (T-30LP & T-30T only)	3" Ball coupler for up to 40,000 lbs GVWR
Models available	
Drop-Deck	12K and up
Drop-Deck Tilt	12K and up
Hydraulic Dump	12K and up
Deck-Over	16K - 30K
Deck-Over Tilt	16K - 30K

Document created on 13 MAR 2025 ©Aebi Schmidt Group, 2023



Monroe Towmaster, LLC | 61381 US Hwy 12 | Litchfield, MN 55355 Phone: 800 462 4517 | www.towmaster.com



