




All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Gooseneck

- Rigid Gooseneck
- 73" Swing Clearance (16" King Pin Setting)
- 2" King Pin
- 8' Steel Top Deck with 2' (45°) Slope in Neck. (10' overall length)
- 2 Built-In Storage Trays With Hinged Lids
- 2 Telescoping Parking Stands
- Stake Pockets (2 Per Side on Top Deck)
- 12k Hydraulic Winch with 3/8" x 60' Cable and Tensioner

Main Deck/Frame

- 102" Load Width
- 39" Deck Height (Fully Loaded)
- Cambered I-Beam Main Frame
- I-Beam Crossmembers mounted 12" On-Center
- 2" Nominal White Oak Decking
- Stake Pockets Mounted Every 4' On-Center on Main Deck

Tail

- 8' Hydraulic Folding Tail with 2" Nominal White Oak Decking
- 4' Hydraulic Fold-Under Approach Ramp with Diamond Tread Plate

Axles/Suspension

- Air Ride Suspension with Dump Valve
- (2) 25,000 lb. Axles (8 Wheels)
- 49" Axle Spacing
- Tires -235/75R17.5 Load Range J, 18-Ply
- 17.5" Wheels, 8-Bolt, Hub Piloted
- Oil Bath Hubs
- Air Brakes (2S/1M) with Full ABS
- Brake Size (12.25 x 7.5)
- Auto Slack Adjusters

Lights/Wiring

- 7 Pole Round Plug
- Rubber Grommet Mounted LED Lights
- Sealed Modular Wiring Harness

Model Features

- Limited Lifetime Frame Warranty - 5 Years
- One-Year Full Warranty
- 5 Year Suspension Warranty
- Weatherproof Registration Holder
- Two-Component Polyurethane Primer and Paint
- Trailer Color: Equipment Black

GAWR (lbs.)	GVWR (lbs.)	Weight (lbs.)	Capacity (lbs.)	Deck Width (in.)	Deck Length (ft.)
45,400	97,120	17,120	80,000	102"	45'
45,400	97,600	17,600	80,000	102"	48'
45,400	98,080	18,080	80,000	102"	53'

Other Options May Be Available. Ask Your Dealer or Visit our Website.

Listed GVWR, weight and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our website or your local authorized dealer for more information.

Options	T-70HT	T-80HT	T-110HT
GOOSENECK/TOP DECK			
9'-4" Rigid gooseneck for use with gooseneck hydraulic ramp (8' hydraulic deck ramp option required)	•	•	•
DECK RAMPS			
8' x Full width of deck hydraulic deck ramp from main deck to top deck. Wood filled with approximate 11° load angle	•	•	•
Star traction over wood on hydraulic deck ramp	•	•	•
7' x 20" manual lift top deck loading ramps, wood filled with spring-assist (Stow away type, flush in deck)	•	•	•
7' x 20" Manual lift top deck loading ramps, wood filled with star traction overlay & spring-assist (Stow away type, flush in deck)	•	•	•
MAIN DECK			
Concentrated load in 10' of Deck	•	•	•
8" On-Center crossmember spacing ILO 12" on-center	•	•	•
Double drop deck (6" Lower deck with approximate 10° angle)	•	•	•
Double Drop Deck (12" Lower deck with approximate 12° angle)	•	•	•
1.5" Apitong wood deck boards ILO white deck (Per linear foot)	•	•	•
9' (108") overall width ILO 8'-6" (102") overall width. (May be subject to permitting) Price per foot of deck	•	•	•
HYDRAULIC TAIL			
1.5" Apitong filled 8' hydraulic tail ILO white oak	•	•	•
Star traction over wood on 8' hydraulic tail	•	•	•
Steel diamond plate ILO white oak on 8' hydraulic tail	•	•	•
Star traction over steel diamond plate on 8' hydraulic tail	•	•	•
Star traction over steel diamond plate on 4' hydraulic fold-under approach ramp.	•	•	•
28" Wide x 3/4" steel square traction aid bars on both the 8' hydraulic tail section and 4' hydraulic fold-under approach ramp, mounted over steel plate every 8" on-center, roadside and curbside (Traction aid track width: 33.5" to 89.5")	•	•	•
TIE DOWNS			
Stake pockets mounted 2' on-center ILO 4'	•	•	•
Additional stake pockets (Per stake pocket)	•	•	•
D-rings in addition to stake pockets (Per D-ring)	•	•	•
Recessed D-rings in decking (Per recessed D-ring)	•	•	•
Two-way chain slot cutouts in outer rails (Per chain slot)	•	•	•
Four-way chain slot cutouts cut into a formed channel down the center of the trailer (per chain slot)	•	•	•
JACK			
25k Two-speed parking jacks ILO drop-pin telescoping parking stands	•	•	•
Dual 25k hydraulic jacks. Includes electric/hydraulic unit (mounted under the rear of the gooseneck)	•	•	•

Options	T-70HT	T-80HT	T-110HT
AXLES/SUSPENSION			
55" axle Spacing ILO 49" axle spacing	•	•	•
60" axle spacing ILO 49" axle spacing	•	•	•
Additional 25k oil bath, air ride suspension axle with dump valve	•	•	•
Air lift front axle (Only available on triple axle configuration)	•	•	•
Hubodometer mounted on the roadside rear axle hub to measure distance traveled (priced per meter)	•	•	•
Air-Weigh digital on-board trailer scale (measure & monitor the weight of the load on the trailer in real time)	•	•	•
Ride height raise/lower kit (Approximately 4" up & 4" down)	•	•	•
TIRES & WHEELS			
255/70R X 22.5, Load Range "H", 16-Ply 10-Bolt Tires & Wheels ILO 235/75Rx17.5 Load Range "J", 18-Ply Tires (Per Tire & Wheel)	•	•	•
Spare tire & wheel 235/75Rx17.5 Load Range "J", 18-Ply (Per tire & wheel)	•	•	•
Spare tire & wheel 255/70R X 22.5, Load Range "H", 16-Ply (Per tire & wheel)	•	•	•
Spare tire carrier mounted under main deck (Lockable)	•	•	•
Spare tire mounting bracket on gooseneck top deck	•	•	•
Polished aluminum wheel (17.5", 8-bolt, hub piloted) ILO steel (Per wheel)	•	•	•
Polished aluminum wheel (22.5", 10-bolt, hub piloted) ILO steel (Per wheel)	•	•	•
Link-Cat's Eye Tire Pressure Equalization System (Balances tire pressures & improve tire longevity) Per axle	•	•	•
Dual Dynamics-Crossfire Tire Pressure Equalization System (Balances tire pressures & improves tire longevity) Per axle	•	•	•
Pressure Systems International (P.S.I.) Tire Inflation System (Automatically Monitors & Adjusts Tire Pressure) Per axle	•	•	•
BRAKES			
Air Brakes, 4S/2M ABS ILO 2S/1M ABS	•	•	•
ELECTRICAL/WINCH			
LED strobe light kit (Switched & mounted)	•	•	•
Flasher kit for marker lights with battery pack	•	•	•
Mid ship L.E.D turn/marker lights (One on curbside & one on roadside of trailer)	•	•	•
Side clearance lights (Per pair)	•	•	•
Winch mounted in slope of gooseneck ILO standard top deck forward placement	•	•	•
20k Hydraulic winch with 120' of 5/8" cable and hook ILO 12k hydraulic winch	•	•	•
Deduct for no winch	•	•	•
Winch Guard (Provides protection for the winch & safeguards it from potential damage)	•	•	•
Recessed winch roller. Helps guide the winch cable smoothly, while reducing friction and wear. Also ensures even feed for better control.	•	•	•
Winch cable tensioner	•	•	•
Corded remote control for winch	•	•	•
Wireless remote for winch	•	•	•
6-Function wireless remote for hydraulics	•	•	•
4-Pole female socket (Per socket)	•	•	•

Options	T-70HT	T-80HT	T-110HT
HYDRAULICS			
12 HP Self-contained hydraulic unit mounted on a platform above winch	•	•	•
20 HP Self-contained hydraulic unit mounted on a platform above the winch	•	•	•
Cover for self-contained hydraulic unit	•	•	•
Hydraulic controls placed on both the roadside & curbside of gooseneck	•	•	•
Dual hydraulics (Enables the trailer to be operated by the self-contained hydraulic unit or tractor wet kit)	•	•	•
PAINT/OTHER			
Trailer Color Options: See standard color chart on page 7	•	•	•
Custom Paint Color: Market price—Please call for cost	•	•	•
Two chock blocks with holders – Mounted under deck between the axles	•	•	•
Flag holders (Per pair)	•	•	•