



All dimensions are nominal. Illustration may be shown with optional equipment.

## Standard Features

### Gooseneck

- 84" Swing Clearance (16" King Pin Setting)
- 2" King Pin
- 50" Loaded Fifth Wheel Height
- Dual Telescopic Parking Stands

### Frame

- 96" Overall Width
- 16" Fabricated I-Beam Main Frame (T1)
- 10" I-Beam Crossmembers
- 48" Sliding Adjustable Fifth Wheel Coupling

### Lights/Wiring

- 7 Pole Round Plug
- Rubber Grommet Mounted LED Lights
- Sealed Modular Wiring Harness

### Axles/Suspension

- Air Ride Suspension with Dump Valve
- (2) 25,000 lb. Axles (8 Wheels)
- 55" Axle Spacing
- Tires -275/70R22.5 Load Range H
- 22.5" Budd Wheels, 10-Bolt, Hub Piloted
- Oil Bath Hubs
- Air Brakes (2S/1M) Non ABS (With Parking Brakes)
- Brake Size (16.5 x 7)
- Auto Slack Adjusters
- Spring Mounted Mud Flaps

### Model Features

- Limited Lifetime Frame Warranty - 5 Years
- One-Year Full Warranty
- 5 Year Suspension Warranty
- Weatherproof Registration Holder
- Two-Component Polyurethane Primer and Paint
- Trailer Color: Equipment Black

GAWR (lbs.)	GVWR (lbs.)	Weight (lbs.)	Capacity (lbs.)	Width (in.)	Length (ft.)
40,560	87,640	7,640	80,000	96"	25'

Other Options May Be Available. Ask Your Dealer or Visit our Website.

Listed GVWR, weight and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our website or your local authorized dealer for more information.

## Options

### GOOSENECK

Gooseneck aluminum fenders (pair)

Aluminum toolbox in gooseneck (Lockable)

Chain/tool storage tray in gooseneck (bolt-on)

Lockable lid for chain/tool storage tray (gooseneck-mounted)

### MAIN DECK

9' (108") overall width ILO 8'-6" (102"). May be subject to permitting.

### AXLES/SUSPENSION

60" axle spread (adds to overall length)

Manual ride height adjustment

Ride height air raise/lower kit (Approximately 4" up & 4" down)

Hubodometer mounted on the roadside rear axle hub to measure distance traveled (priced per meter)

Air-Weigh digital on-board trailer scale (Allows you to measure and monitor the weight of the load on the trailer in real time)

### BRAKES

Air brakes, 2S/1M ABS

Air brakes, 4S/2M ABS

### TIRES/WHEELS

Spare tire & steel wheel 275/70R X 22.5, Load Range "H", 16-Ply (Per tire & steel wheel)

Spare tire mounting bracket on gooseneck

Polished aluminum wheel (22.5", 10-bolt, hub piloted) ILO steel (Per wheel)

Link Cat's Eye Tire Pressure Equalization System (balances tire pressures and improves tire longevity) Per axle

Dual Dynamics Crossfire Tire Pressure Equalization System (balances tire pressures and improves tire longevity) Per axle

Pressure Systems International (P.S.I.) Tire Inflation System (Automatically Monitors & Adjusts Tire Pressure) Per axle

### OTHER

Jeep Color Options: See standard color chart on page 7

Custom Paint Color: Market Price—Please call for cost

Two chock blocks with holders—Mounted under frame

Flag holders (Per pair)